

SPECIFICATION SHEET | KTD

Product Name: KLIME-EZEE Truck Dock Platform Range | KTD
Safe Working Load (SWL): 500 kg

Product Overview:

The **KLIME-EZEE Truck Dock Range (KTD)** is specifically designed for efficient loading and unloading of vehicles. This durable and robust range is perfect for environments where safe and stable access to truck beds, containers and machinery is essential. Its ergonomic design prioritises user safety while ensuring smooth operations. Popular in logistics centres, warehouses, and distribution hubs, this range is built to withstand heavy use.



Key Features:

- **Heavy-Duty Construction:** Reinforced treads, box section base and structure to support up to 500 kg.
- **High SWL tolerance:** Designed to handle heavy loads securely.
- **Extra-Large Platform:** Generous working area 700 mm (w) x 1200 mm (d), ideal for loading/unloading trucks and carrying out maintenance.
- **Customisable Exit Options:** Side exit with chains as standard, or optional gates / fixed sides.
- **Customisable Colours and Treads:** Available with six different colour options and two tread types.
- **Ready-to-Use:** Fully welded and ready for immediate use upon delivery.

Model Variants and Specifications:

Product Code	Treads	Working Platform Height	Work Height	Overall Height	Overall Width	Overall Length	Weight	Brake Type
KTD 05	5	1000	2000 - 2750	2000	995	2100	66	Side brake
KTD 06	6	1200	2200 - 2950	2200	995	2300	97	Side brake
KTD 07	7	1400	2400 - 3150	2400	995	2500	128	Side brake
KTD 08	8	1600	2600 - 3350	2600	1080	2700	158	Side brake
KTD 09	9	1800	2800 - 3550	2800	1080	2900	189	Side brake

Please note: All dimensions are approximate and shown in mm, with weights shown in kg.

Due to our ever-improving environment, we may make enhancements to our products which affect dimensions. Therefore we reserve the right to amend these at any time to better serve our customers. To confirm the spec go to : klime-ezee.com/ktd.

Technical Details:

- **Angle of ascent:** 45 degree, enabling you to walk down the steps forward facing.
- **Overall Width:** The main framework is approximately 750 mm (w). The listed width is the maximum point, measured at the axle.
- **Working Platform Size:** Standard platform size is 700 mm (w) x 1200 mm (d).
- **Tread Dimensions:** Each tread is 700 mm (w) x 200 mm (d), offering secure footing.
- **Strengthened Treads:** Tread reinforcements at the front of each tread, including the platform.
- **Platform Toe Plate:** This range comes with NO toe plate on the working platform as standard.
- **Chain Information:** Top chain height approx. 950 mm; lower chain height approx. 560 mm.
- **Rear Legs:** These splay out from the unit at an approximate 3 degree angle.

Applications:

The KTD range is suitable for various environments where space is limited, including:

- Warehouses
- Loading and unloading vehicles
- Industrial settings

Maintenance Recommendations:

To ensure ongoing safety and performance, a maintenance inspection every six months is recommended. You can visit our website for more information.

Document last updated 22.11.2024